



protective coatings and resin flooring

PRODUCT DATA

API CLEANER PLUS

PRODUCT DESCRIPTION

API Cleaner Plus is a concentrated floor finish stripper/reliquifier designed for periodic floor maintenance. This heavy-duty cleaner effectively removes aged wax sealers, oils, organics, and even detergent-resistant finishes. API Cleaner Plus requires no agitation or scrubbing to remove floor finishes. When used on surfaces finished with API Wax or another wax-based sealer, a new application of API Wax is required.

TYPICAL USES

API Cleaner Plus is used for the removal of floor finishes, especially API Wax, from all types of floor surfaces. It is safe for use on all API materials.

PRODUCT ADVANTAGES

- Biodegradable
- Reliquifies old floor finishes
- No scrubbing required
- Highly concentrated
- Safe on most hard floor surfaces

APPLICATION

Apply properly diluted API Cleaner Plus liberally to the floor. Allow the solution to stand for 5-10 minutes, keeping the entire floor area wet. Do not allow to dry. Pick up the solution with a squeegee-equipped wet vacuum. Rinse the floor with clean water. After the floor is dry, proceed with a new application of API Wax.

Note: API Cleaner Plus may also be used in a conventional stripping operation utilizing a floor machine equipped with a stripping pad. In this case, API Cleaner Plus should be used with a dilution ratio of 6-8 oz. per gallon of water.

PACKAGING

API Cleaner Plus is packaged in 2.5 gallon jugs and nets 10 kg (22.0 lb) of concentrated liquid.

STORAGE CONDITIONS

Store API Cleaner Plus between 16 and 30°C (60 and 86°F) in a dry area. Do not freeze.

DILUTION

Because API Cleaner Plus is packaged in a concentrated form, it must be diluted for use. Dilution can be accomplished with hot or cold water using the below dilution ratios.

Light Wax Build-up.....	16 oz. per gallon of water
Medium Wax Build-up.....	32 oz. per gallon of water
Heavy Wax Build-up.....	64 oz. per gallon of water
Extra Heavy Wax Build-up.....	128 oz. per gallon of water

RECOMMENDATIONS

- The dilution ratios stated are approximations. Adjust the dilution ratio to optimize cleaning performance or to affect greater economy.
- Dispose of waste materials in accordance with government regulations.

PRECAUTIONS

- The use of safety glasses and impervious gloves is required during application.
- Avoid contact with all liquids as they may cause skin and/or eye irritation. In case of contact, flush the area with copious amounts of water for at least 15 minutes and seek medical attention.
- Wash hands thoroughly with soap and warm water after use.
- Use only with adequate ventilation.

API USA believes the information heretofore to be true and accurate as of the date of publication. API USA makes no warranty, expressed or implied, based on this literature and assumes no responsibility for consequential or incidental damages in the use of the systems described, nor does it accept liability for the performance or application of its products, as application is executed by personnel outside the contractual ties of API USA. API USA reserves the right to modify and change products or literature at any time and without prior notice.